

**MINIMUM CLEARANCES REQUIRED FROM COMBUSTIBLE MATERIAL –
(WITH THE HEAT SHIELD FITTED WHERE APPLICABLE)**

MODEL	SIDE OF STOVE	BEHIND THE STOVE	ABOVE THE STOVE
RUNSWICK MK1,2 & 3	150 mm	N/A	300 mm
ROSEDALE INSET	200 mm	N/A	350 mm
FARNDALE	450 mm	350 mm	300 mm
RYEDAILE	450 mm	350 mm	300 mm
LITTLE THURLOW *	450 mm	350 mm	300 mm
WHISPERDALE	450 mm	350 mm	300 mm
DALBY S/C *	650 mm	500 mm	300 mm
SALTBURN S/C *	650 mm	500 mm	300 mm
ROSEDALE *	550 mm	850mm	400 mm
CAEDMON *	550 mm	850 mm	400 mm
CAEDMON OPTION *	300 mm	410 mm	400 mm
LANGDALE *	400 mm	200 mm	400 mm
THORNTONDALE	650 mm	350 mm	400 mm
BRANSDALE	650 mm	350 mm	400 mm
WELBURN LOW / TALL	600 mm	900 mm	450 mm
GLAISDALE	600 mm	450 mm	450 mm
BYLAND	600 mm	900 mm	450 mm
BRANSDALE DOUBLE *	450 mm	350 mm in front of both doors	400 mm
WELBURN DOUBLE	750 mm	900 mm in front of both doors	450 mm

* = These models suitable for a 12mm Hearth