

MINIMUM CLEARANCES REQUIRED FROM COMBUSTIBLE MATERIAL – (WITH THE HEAT SHIELD FITTED WHERE APPLICABLE)

MODEL		SIDE OF STOVE	BEHIND THE STOVE	ABOVE THE STOVE
RUNSWICK MK 2		150 mm	N/A	300 mm
ROSEDALE INSET ECO S/C		200 mm	N/A	350 mm
LITTLE THURLOW	*	450 mm	350 mm	300 mm
LITTLE THURLOW ECO S/C	*	450 mm	350 mm	30 mm
CROPTON S/C	*	350 mm	450 mm	300 mm
DALBY S/C ECO / SALT BURN S/C	*	650 mm	500 mm	300 mm
PICKERING ECO W/B S/C	*	450 mm	250 mm	300 mm
HARROGATE ECO S/C	*	400 mm	200 mm	400 mm
CAEDMON ECO S/C	*	400 mm	200 mm	400 mm
ROSEDALE S/C	*	550 mm	850mm	400 mm
LANGDALE / LANGDALE ECO	*	400 mm	200 mm	400 mm
THORNTONDALE		650 mm	350 mm	400 mm
BRANSDALE		650 mm	350 mm	400 mm
HARROGATE	*	525 mm	475 mm	400 mm
ROSEDALE S/C	*	550 mm	850mm	400 mm
WELBURN LOW / TALL	*	600 mm	900 mm	450 mm
GLAISDALE		600 mm	450 mm	450 mm
BYLAND		600 mm	900 mm	450 mm
BRANSDALE DOUBLE	*	450 mm	350 mm in front of both doors	400 mm
WELBURN DOUBLE	*	750 mm	900 mm in front of both doors	450 mm